



IIoT Gateway EPG-005 S SPECIFICATIONS:

Hardware	CPU	Quad Core ARM 64 bits
	NPU	0.8 TOPS
	Storage	16GB
	Cellular	4G
	RTC	Real Time Clock
	LAN	1 x LAN, Support DHCP Server
	USB	2 x USB
	RS485	1 x RS485
	HDMI	1 x HDMI
Electrical Parameters	Rated Voltage	DC9~24V (Working Range)
	Rated Power	5W
	Power Protection	Anti-Static, Anti-Surge, Anti-Reverse
	Certification	CE
Environmental Parameters	Operating Temperature	-20 ~ 70°C
	Storage Temperature	-20 ~ 70°C
	Environment Humidity	10-90%RH (Non-Condensing)
	Cooling Method	Heat Sink / Dissipation Silicone
Screen	Screen Size	7 Inches
	Resolution	1024 x 600px
	Type	Capacitive Touch Screen
Software Parameters	Ops	Support remote configuration/Upgrade/Management
	VPN	Support intranet penetration
	Edge Computing	Support drag and drop programming Support zero-code development Support JavaScript development
	Data Storage	Support TSDB (Time Series Databases)
	Industrial Agreement	Support multiple industrial protocols Modbus RTU/TCP, Siemens, OPC UA, HTTP, MQTT, ARP, QoS, SNMP, Telnet, SSH



CONTACT US
www.epithos.com

 epithos.iot

 epithos

