



IOT Gateway EPG-003 SPECIFICATIONS:

Processor System	CPU	64 bit Quad-Core Intel N100 Processor
	BIOS	EFI BIOS
Memory	Technology framework	Single channel DDR4 2133Mhz
	Memory	8GB
	Socket	DDR4 SODIMM 60 Socket
Video	Graphic controller	Intel UHD 600 Graphics
	HDMI	HDMI (2.0) MAX resolution 4K@60Hz
	VGA	VGA MAX resolution 1920x1200
I/O rear panel	Ports	1 x HDMI, 2 x USB3.0, 4 x USB2.0, 2 x LAN, 6 x COM 1 x Quick boot button with indicator light, 1 x Reset button, 1 x DC 1 x Power indicator light, 1 x Hard disk indicator light
Network	Controller	2 x Gigabit Ports
Input/Output Interface	USB	4 x USB2.0, 2 x USB3.0 Max support +5V/1A
	Com Port	2 x RS485 Ports
Expansion Bus	Mini-PCIe	1 Mini-PCIe socket, support PCIe and USB device
Storage	SATA	1 standard SATAIII interface with a maximum transfer rate of 6Gb/s
	M-SATA	1*Mini-PCIe M-SATA Scket, Support SANDISK protocol
	EMMC	Support 32/64/128G(optional)
Power supply	Power Type	Single input dc power supply, DC12-19V
Working Environment	Operating temperature	-20°C ~ +60°C
	Storage temperature	-40°C ~ +85°C
	Working humidity	0% ~ 90% relative humidity, no condensation
	Storage humidity	0% ~ 90% relative humidity, no condensation
Protocol	Network Protocol	MQTT / HTTP / TCP / UDP / WEBSOCKET
Device	OS	Linux
	Size	165 x 125 x 53 mm
	Weight	0.5KG
	Certification	CE, ROHS, FCC



CONTACT US
www.epithos.com

 epithos.iot

 epithos

